

MODEL P329

Battery powered plastic strapping tool for demanding applications



FEATURES

- To be used with Polyester (PET) and Polypropylene (PP) plain and embossed strapping; capable of handling strap sizes up to $\frac{3}{4}$ " (19mm)
- High Tension Force up to 900 lbs.
- Brushless motor for less maintenance and improved life time
- Motor temperature monitoring to protect motor from overheating
- Improved plates and guides – less effort required to remove the tool from the strap
- Simple one-handed operation

MODEL P329

Battery powered plastic strapping tool for demanding applications

© September 2017 - 122955B

STANDARD FEATURES

Samuel Packaging Systems Group is pleased to introduce the P329, a hand held battery operated tool for demanding applications. Capable of handling strap sizes up to 3/4" (19mm), the P329 features a brushless motor for less maintenance and an improved life time. Featuring improved plates and guides, the P329 requires less effort to remove the tool from the strap after application. The P329 is available as a two button tool, able to operate in a manual or semi-automatic manner.

SPECIFICATIONS

Strapping Qualities	Polyester (PET) and Polypropylene (PP) plain and embossed	
Strapping Width	16.0 - 19.0 mm	5/8 - 3/4"
Strapping Thickness	0.65 - 1.35 mm	.026 - .053"
Weight (incl. battery)	4.2 kg	9.3 lbs
Dimension	L 351 x W 134 x H 143 mm	L 13.8" x W 5.3" x H 5.6"
Type of Seal	Friction weld sealing	
Average Seal Strength	approx. 75 % (dependent on strap quality)	
Tension Force	500 - 4000 N	112 - 900 lbs (adjustable)
Tensioning Speed	49 - 79 mm/s	1.9 - 3.1 inch/s
Power Supply	Battery Li-Ion 18 VDC / 4.0 Ah	
Suspension Bracket	(optional)	

Specifications are for guidance purposes only and subject to change without notice.

CHART OF TYPES MODEL P329

Item No.	Model	Strap Widths		Strap Thicknesses		Max. Tension		Tension Speed	
		mm	in	mm	in	N	lbs	mm/sec.	inch/sec.
43.2522	P329/16/0.65-1.05	16.0	5/8	0.65 - 1.05	.026 - .041	4000	900	49 - 79	1.9 - 3.1
43.2532	P329/19/0.65-1.05	19.0	3/4	0.65 - 1.05	.026 - .041	4000	900	49 - 79	1.9 - 3.1
43.2533	P329/19/1.06-1.35	19.0	3/4	1.06 - 1.35	.042 - .053	4000	900	49 - 79	1.9 - 3.1

BATTERY CHARGERS FOR MODEL P329

Item No.	Charging Type	Voltage / Frequency	Countries
N5.4447	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV

REPLACEMENT BATTERY FOR MODEL P329

Item No.	Battery	Voltage	Capacity	Charging time
N5.4349	Accu Li-Ion	18 VDC	4.0 Ah	approx. 80 min.

ACCESSORIES

Item No.	
P32.0223	Suspension bracket
P32.0224	Wearing plate (metal) for rough and hard surfaces
P32.0225	Protection plate (plastic) to protect complete bottom side
P32.0228	Motor cooling fan
N7.5154	Cycle count reader

We invite you to experience the Samuel advantage by contacting us today!

packaging@samuel.com

Canada: 800-607-8727
U.S.: 800-323-4424


SAMUEL
PACKAGING SYSTEMS GROUP