

Customized Stretch Wrappers with Advanced Technology since 1994

3300-CTA

Conveyorized Automatic

FILM TAIL TREATMENT - ALL ELECTRIC:

- ❖ Electric actuated film clamp mechanism
- ❖ Electro-mechanically actuated film tail cut/wiper arm mechanism
- ❖ Ni-chrome impulse hot wire film cut off c/w automatic periodic cleaning cycle

FILM CARRIAGE - Less film slippage means more consistent stretch and the “sticky” side of the film will always be against both the rubber rollers and the load where it belongs.

ALL ELECTRIC - no pneumatic lines or noisy air compressors required



SYSTEM CONFIGURATION – Designed to be installed with existing product flow and conveyor layout design. Whether In-line or off-line, the automation package is designed to be in-line with conveyors using interface relays/logic or off-line standalone system using a wireless remote.

TOLL FREE: 888-209-4344 PH: 905-678-6655 FAX: 905-678-3429

www.cousinpackaging.com

3300-CTA DESIGN FEATURES/SPECIFICATIONS

PRODUCTION RATE:

Rated for 40 loads per hour depending on load sizes and number of wraps

LOAD CAPACITY:

- ❖ 4000# Capacity
- ❖ 48" L x 48" W x 75" H max load size (24" minimum height)

NOTE: Larger load size options are available

CONVEYORS:

- ❖ 2.5" diameter rollers on 3" centers
- ❖ 50" effective roller width –
- ❖ 16.5" standard passline height
- ❖ AC Drives



CONTROLS:

- ❖ LCD Operator Interface with Diagnostics
- ❖ Separate UP/DOWN Spiral Speed Controls
- ❖ 3 Separate Wrap Programs
- ❖ Selectable Reduced Film Tension parameters for wrapping top and/or bottom of light loads
- ❖ Emergency Stop button
- ❖ NEMA 12

3 Year Warranty on Components



FILM CARRIAGE:

- ❖ *Super Rapid Thread II™* 20" capacity pre-stretch film carriage
- ❖ Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside on the load
- ❖ AC variable speed motor
- ❖ 33% to 313% fixed stretch capability
- ❖ Carriage Descent Safety Shut-Off Device
- ❖ Superior *film-to-roller* contact area
- ❖ *Lifetime warranty on pre-stretch rollers*



TOWER DESIGN:

- ❖ Fully Enclosed & Guarded Motors
- ❖ No Exposed Cables
- ❖ Heavy Duty Formed/Structural Steel
- ❖ Electro-static powder coated paint finish
- ❖ *5 Year Warranty on Steel Fabrications*



The Association for Packaging and Processing Technologies